

EZ LYNK AUTO AGENT 3 INSTALLATION INSTRUCTIONS

Installation Guide

Read the complete guide before beginning. Keep removed hardware organized, follow all safety precautions, and verify all connections before operating the vehicle.



I. Quick Start Guide

1. Purchase the Device & Include Your VIN Number
2. Flash your truck BEFORE installing any hardware components
3. Hook up a Battery Charger and set it to 10A
4. Plug the Auto Agent into your OBD-II port
5. Connect to Auto Agent via Wi-Fi
6. Connect to your Technician
7. Go to ECU Profiles & Flash Your Tuning

II. Detailed Step-by-Step Guide

STEP 1

Buy an EZ-Lynk with 4-Week Lynk (Limited) or Lifetime Lynk (Unlimited) Support.

When you place your order, we require the VIN Number of your truck. This allows us to link your vehicle to the device prior to shipment. Most orders are shipped via expedited service. So getting us the VIN when you place your order ensures we can get you your EZ-Lynk as fast as humanly possible.

STEP 2

Tune your truck before removing hardware components.

Make sure that you tune your truck before you even think about removing your EGR or Exhaust Systems. This way, if you have any trouble tuning your truck, this prevents unnecessary downtime in the event of a flashing issue.

Hook up a battery charger. STEP 3

Before you start, grab your battery charger and hook it up to the truck. It does not matter if you have brand-new batteries or recently charged them to 100%. If you don't have a battery charger, get one and set it to a 10A charge. Modern ECMs are highly sensitive to voltage fluctuations.

Download the EZ-Lynk App. STEP 4

Go to the App Store or the Google Play Store and download the EZ-Lynk Auto Agent App. Once the app has been downloaded and installed you can go ahead and make an account.

Plug the EZ-Lynk into your OBD-II port. STEP 5

You're ready to plug the EZ-Lynk into your OBD-II port under the dash. If you're flashing an 18+ Cummins you will need to connect the Bypass Cable at the same time. It only needs to be plugged in while you flash your tunes, however, it may remain connected if desired. In that case, you can run it through the firewall of the truck.

Connect to the Auto Agent. STEP 6

Open your Wi-Fi settings and connect to the Auto Agent via Wi-Fi on your phone or tablet. Once you are connected you can open the app, and the Auto Agent should detect your VIN and recognize the connection.

Go ahead and accept this, You will be prompted to enter basic vehicle information, once completed, your tuning files will be auto-populated onto your device. You'll start to get push notifications as each file comes through into your account.

Flash Your Tuning. STEP 7

Now that you're connected, the app will default to the main dash- board. From there you can select the button in the top-left corner of the screen to open the menu. From there, you select your vehicle, your truck should show up as the vehicle and give you a list of further options. Select ECU Profiles from that screen, this is where your tune files are stored, you'll see a list of files.

After downloading the file, select "Install". The app will guide you through the required Key-On/Key-Off procedure while the flash process completes. Once the tune has flashed into the truck, it will now say Installed under the tune file. Ford and GM vehicles require a separate TCM flash. If you have a Dodge, the TCM Tuning is pack- aged with Engine Tuning and only requires a single flash.

